

WHAT IS CLAIMED IS:

1. A wavelength-division multiplexing optical communication system in which an optical lossy medium, optical amplifiers and Raman amplifiers for
5 compensating for loss in the optical lossy medium are cascade-connected, said system comprising:
 means, which is provided in an optical amplifier, for correcting slope of a wavelength characteristic produced by wavelength-dependent loss of the optical
10 lossy medium;
 acquisition means for acquiring state of use of a Raman amplifier, at a node the same as that of the optical amplifier, in a link opposing a link in which said optical amplifier exists, or state of use of a
15 Raman amplifier at a node downstream of said optical amplifier; and
 means for deciding, based upon the state of use of the Raman amplifier, whether or not to cause the optical amplifier to perform a slope correction.
- 20 2. The system according to claim 1, wherein said acquisition means includes:
 means for demultiplexing light of a monitoring control signal from main-signal light; and
 means for acquiring, from the light of the
25 monitoring control signal in a link opposing that of said optical amplifier, the state of use of a Raman amplifier at a node downstream of said optical amplifier.
3. The system according to claim 1, further comprising
30 an external control unit for ascertaining the state of use of a Raman amplifier at each node based upon a monitoring control signal sent and received at each node together with main-signal light; wherein said acquisition means acquires, from said external control
35 unit, state of use of a Raman amplifier at a node downstream of said optical amplifier.
4. A wavelength-division multiplexing optical communication system in which an optical lossy medium, optical amplifiers and Raman amplifiers for
40 compensating for loss in the optical lossy medium are cascade-connected, said system comprising:
 means, which is provided in an optical amplifier, for correcting slope of a wavelength characteristic produced by wavelength-dependent loss of the optical

lossy medium;

acquisition means for acquiring state of flattening-control implementation which indicates whether a Raman amplifier is implementing control to
5 flatten a wavelength characteristic at a node downstream of the optical amplifier, based upon the wavelength characteristic on an input side or output side of said optical amplifier connected to said Raman amplifier; and

10 means for deciding whether or not to cause said optical amplifier to perform a slope correction based upon the state of flattening-control implementation by said Raman amplifier.

5. The system according to claim 4, further comprising:
15

a spectrum analyzer for detecting the wavelength characteristic on an input side or output side of said optical amplifier connected to said Raman amplifier; and

20 means provided in the Raman amplifier for performing flattening control based upon the wavelength characteristic detected by said spectrum analyzer.

6. The system according to claim 1, wherein said acquisition means includes:

25 means for demultiplexing light of a monitoring control signal from main-signal light; and

means for acquiring, from the light of the monitoring control signal in a link opposing that of said optical amplifier, the state of flattening-control
30 implementation at a node downstream of said optical amplifier.

7. The system according to claim 4, further comprising an external control unit for ascertaining the state of flattening-control implementation by a Raman amplifier
35 at each node based upon a monitoring control signal sent and received at each node together with main-signal light; wherein said acquisition means acquires, from said external control unit, the state of flattening-control implementation by a Raman amplifier.

40 8. A wavelength-division multiplexing optical communication system in which an optical lossy medium, optical amplifiers and Raman amplifiers for compensating for loss in the optical lossy medium are cascade-connected, said system comprising:

slope-correction control means, which is provided in a Raman amplifier, for correcting slope of a wavelength characteristic produced by wavelength-dependent loss of the optical lossy medium;

5 means for calculating amount of slope correction based upon amount of tilt of a wavelength characteristic of a transmission line produced between said Raman amplifier and a node at a receiving end; and
10 means for setting the amount of slope correction in said slope-correction control means of said Raman amplifier; wherein slope correction is performed solely by said Raman amplifier.

9. The system according to claim 8, wherein said slope-correction control means calculates amount of
15 tilt of a wavelength characteristic at an input section of each optical amplifier and calculates a necessary amount of slope correction from this amount of tilt.

10. The system according to claim 8, wherein there is provided a spectrum analyzer for detecting a wavelength
20 characteristic at an input section of each optical amplifier; and

said slope-correction control means calculates amount of tilt of a wavelength characteristic at an input section of each optical amplifier based upon
25 result of detection by said spectrum analyzer, and calculates a necessary amount of slope correction from this amount of tilt.

11. The system according to claim 10, wherein a wavelength characteristic at an input section of a
30 optical amplifier devoid of a spectrum analyzer is calculated by interpolation using a wavelength characteristic at an input section of an optical amplifier having a spectrum analyzer.

12. The system according to claim 8, further
35 comprising:

a spectrum analyzer for detecting a wavelength characteristic at an input section of an optical amplifier; and

a flattening controller provided in a Raman
40 amplifier for flattening a wavelength characteristic detected by said spectrum analyzer; wherein a slope correction is performed by adding amount of correction by flattening control to amount of correction by slope-correction control.

13. A wavelength-division multiplexing optical communication system in which an optical lossy medium, optical amplifiers and Raman amplifiers for compensating for loss in the optical lossy medium are cascade-connected, said system comprising:

5 slope-correction control means, which is provided in a Raman amplifier, for correcting slope of a wavelength characteristic produced by wavelength-dependent loss of the optical lossy medium; and
10 means for calculating amount of slope correction by the Raman amplifier by subtracting, from an overall amount of tilt of a wavelength characteristic produced between said Raman amplifier and a node at a receiving end, an amount of slope correction by optical
15 amplifiers that exist between said Raman amplifier and said node, and setting the calculated amount of slope correction in said slope-correction control means; wherein said Raman amplifier performs a slope correction based upon the set amount of slope
20 correction.

14. A wavelength-division multiplexing optical communication system in which an optical lossy medium, an optical amplifier and a Raman amplifier for compensating for loss in the optical lossy medium are cascade-connected, said system comprising:

25 slope-correction control means, which is provided in each of an optical amplifier and Raman amplifier wherein amount of slope correction is limited, for correcting slope of a wavelength characteristic
30 produced by wavelength-dependent loss of the optical lossy medium; and

means for acquiring information concerning wavelength-dependent loss of the optical loss medium between nodes and amount of slope correction by each
35 optical amplifier and Raman amplifier, calculating from this information and amounts of slope correction an amount of tilt of a wavelength characteristic at an input section of each optical amplifier, deciding amounts of slope correction by optical loss
40 compensators in order from an upstream side using the amount of tilt, and repeating the above control with respect to a downstream node when the amount of slope correction has exceeded the capability of an optical loss compensator, thereby deciding and setting amount

of slope correction by each optical loss compensator;
wherein said optical loss compensator performs a slope
correction using the set amount of slope correction.

15. The system according to claim 14, further
5 comprising:

a spectrum analyzer for detecting a wavelength
characteristic at an input section of the optical
amplifier; and

a flattening controller provided in a Raman
10 amplifier for flattening the wavelength characteristic
detected by said spectrum analyzer; wherein the slope
correction is performed by adding the amount of the
slope correction control and the amount of the
flattening control.

16. The system according to claim 14, wherein there is
15 provided a spectrum analyzer for detecting a wavelength
characteristic at an input section of each optical
amplifier;

amount of tilt of a wavelength characteristic at
20 an input section of each optical amplifier is
calculated based upon result of detection by said
spectrum analyzer.

17. The system according to claim 16, wherein a
wavelength characteristic at an input section of a
25 optical amplifier devoid of a spectrum analyzer is
calculated by interpolation using a wavelength
characteristic at an input section of an optical
amplifier having a spectrum analyzer.

18. The system according to claim 14, wherein
30 correction of calculated amount of tilt is performed
not only by optical amplifiers and Raman amplifiers but
also by devices such as gain equalizers inserted into
said system.